

# **Double Carcass Submarine Hose**



EMSTEC provide a range of high quality, high performance, oil suction and discharge hoses, extensively used at offshore moorings throughout the world. The EMSTEC Double Carcass Submarine hoses are utilized in high integrity sub-sea installations such as MBM, CALM, SALM configurations (i.e. Steep 'S', Lazy 'S', Chinese Lantern).

In addition to standard hose carcass (commonly termed 'primary' carcass), EMSTEC Double Carcass Submarine hoses incorporate an additional second carcass designed to contain any product escape from the standard carcass as a result of a slow leak or sudden failure. Effective, robust and reliable leak detection and indication system is provided.

The EMSTEC Double Carcass Submarine hoses fully comply with the requirements of the "Guide to Manufacturing and Purchasing Hoses for Offshore Moorings, OCIMF/GMPHOM 2009 - 5th Edition".

All hoses are designed and manufactured under a quality system in accordance with ISO 9001.

For performance characteristics and specification, please refer to EMSTEC data sheet 'Double Carcass Hose Specification'.

### 22210 SDC - End Reinforced without float collars (i.e. under Buoy)



22310 SDCF - End Reinforced with float collars (i.e. under Buoy) \*



### End Reinforce th Collars - DC

EMISTEC GmbH Gewerbering 8 - 22113 Oststeinbek Tel. +49 (0)40 79 686 345 · Fax +49 (0)40 79 686 702 e-mail: info@emstec.net · web; www.emstec.net

\*Note: Number and distribution of float collars can be adjusted to suit client specific requirements.



## Double Carcass Submarine Hose (continuation)

**'22' SERIES** 

22240 DSC - Both Ends Reinforced without float collars



22250 DSC - Reducing Hose without float collars



22260 DSC - Tail Hose without float collars



22270 DSC - Tanker Rail





# **Double Carcass Hose** Specification

## **'22' SERIES**

EMSTEC Double Carcass Submarine, Floating & Catenary hoses fully comply with the requirements of the "Guide to Manufacturing and Purchasing Hoses for Offshore Moorings, OCIMF/GMPHOM 2009 - 5th Edition".

### **PERFORMANCE CHARACTERISTICS & CONSTRUCTION**

Nominal Bore (mm):	150 (6"), 200 (8"), 250 (10"), 300 (12"), 400 (16"), 500 (20"), 600 (24") (non-standard diameters available on request)
Standard Length:	9.1M (30'), 10.7M (35') & 12.2M (40') (non-standard less than 12.2M also available)
Hose Construction:	Liner Tube – NBR based Rubber, resistant to hydrocarbons with aromatic content up to 60%
	Primary Carcass – Elastomer reinforced with multi-layers of high tensile textile cords and embedded steel wire helix.
	Secondary Carcass - Elastomer reinforced with multi-layers of high tensile textile cords
	Floatation Material (Floating Hoses only) – Closed cell foam
	Outer Cover – Fibre reinforced smooth elastomer cover, resistant to ageing, abrasion, weathering, sunlight, tearing and oil and seawater penetration. (Polyurethane coating available on request).
Flanges:	ANSI B16.5 Class 150 or 300 Flat Face (FF) or Raised Face (RF), Hot Dip Galvanisation in accordance with BS729 Part 1, EN ISO 1461
Pressure Rating:	Primary Carcass - 15 BAR (225 PSI), 19 BAR (275 PSI), 21 BAR (305 PSI) (higher pressure ratings on request)
	Secondary Carcass - 15 BAR (225 PSI), 19 BAR (275 PSI), 21 BAR (305 PSI)
Minimum Burst Pressure:	Primary Carcass - 75 BAR (1090 PSI), 95 BAR (1375 PSI), 105 BAR (1525 PSI)
	Secondary Carcass - 30 BAR (435 PSI), 38 BAR (550 PSI), 42 BAR (610 PSI)
Flow Velocity:	Maximum of 21m/s
Fluid Product:	Crude Oil and Liquid Petroleum Products (other than liquefied petroleum gases and liquefied natural gases).
Temperature Range:	Fluid Temperature from -20°C to 82°C.
	Ambient Temperature from -29°C to 52°C.
Minimum Bend Radius:	Submarine Hoses - 4 x hose Nominal Bore Diameter.
	Floating Hose – 6 x hose Nominal Bore Diameter.
Electrical Continuity:	Electrically Continuous or Discontinuous as required.
Leak Detection:	Pressure compensated leak detection system for Floating, Submarine & Catenary applications.

For information regarding hose types and applications, please refer to relevant EMSTEC hose data sheets.

### **DESIGN APPROVAL & QUALITY ASSURANCE**

All of the hoses are designed and manufactured under a quality system in accordance with ISO 9001.

Prototype Hose manufacture and testing witnessed and verified by Bureau Veritas & Det Norske Veritas (Certifying Authorities) and GDC International (Industry Consultants).

> **I**QNet CERTIFICATE

ISO 9001

Manufacture





		8
	Return of Augho	100
	NUMBER OF STREET	-
Taxa and a	in in 10 min at Rodag Maaroo I Martin (10 min andres - 10 min 1 mil 10 min angewer - 10 min 1 min (10 min angewer - 10 min	transpirate and the second
_		ung

Tentras Int A Qualification at UR Incline, and Discharge, Reco
An Alexandro and Analysis and A
Restored and the second s
B. And Article B. W. William (2017). This is the comparison of the comparison of the comparison of the comparison of the comparison of the P. And and Antiphetic and the comparison of the comparison of the comparison of the comparison of the comparison of the antiphetic and the comparison of the comparison of the antiphetic an
A provide apply the least is an allow once formers. From an addition of the set
F
To accurate the priority for some server

Prototype Approval (GDC)

ISO 9001 Desian

EMSTEC GmbH

Gewerbering 8 - 22113 Oststeinbek Tel. +49 (0)40 79 686 345 · Fax +49 (0)40 79 686 702 e-mail: info@emstec.net · web: www.emstec.net

Prototype Approval (BV)

Prototype Approval (DNV)